

Model	6K	8K	10K	12K	15K	20K	25K	30K
Input (PV DC)								
Max. PV input power (W)	9000	12000	15000	18000	22500	30000	37500	45000
Rated PV input voltage (V)	690							
Number of independent MPPT inputs	2/(2:2)			3/(2:2:2)				
Max. PV input voltage (V)	1000							
MPPT voltage range (V)	200~900							
Start-up voltage (V)	100							
Max. PV input current per MPPT (A)	20/20			40/40/40				
Max. PV short-circuit current input per MPPT	25/25(A:1/B:1)			50/50/50(A:2/B:2/C:2)				
Battery								
Compatible battery type	Lithium-ion/Lead-Acid							
Rated battery voltage (V)	400							
Battery voltage range (V)	100~700							
Max. charging voltage (V)	700							
Max. charging/discharging current (A)	50							
Max. charging/discharging power (W)	6000	8000	10000	12000	15000	20000	25000	30000
Force wake up battery from PV function	YES							
Grid								
Rated AC voltage (V)	3L/N/PE, 230/400Vac							
Rated AC frequency (Hz)	50							
Rated AC output current (A)	9.1	12.2	15.2	18.2	22.8	30.3	36.3	45.6
Rated AC output power (W)	6000	8000	10000	12000	15000	20000	25000	30000
Max. AC intput current (A)	13.6	18.2	22.8	27.3	34.1	45.5	56.8	68.2
PF	0.99 (Adjustable from 0.8 leading to 0.8 lagging)							
THDI	<3%							
Max. continuous AC passthrough current (A)	75							
GEN								
Rated GEN voltage (V)	3L/N/PE, 230/400Vac							
Rated GEN frequency (Hz)	50							
Rated GEN input current (A)	30							
Rated GEN input power (W)	12000							
Rated GEN current of BYPASS relays (A)	60							
UPS								
Rated output power (W)	6000	8000	10000	12000	15000	20000	25000	30000
Rated output voltage (V)	3L/N/PE, 230/400Vac							
Rated output current (A)	9.1	12.2	15.2	18.2	22.8	30.3	36.3	45.6
Rated output frequency (Hz)	50							
Surge power, duration	1.5Pn, 10s							
Switching time	20ms							
Wave form	Sine wave							
THDV	<3%							
Efficiency								
Max. efficiency	97.4%							
Max.charge/discharge efficiency	97.2%							
Protection								
PV reverse polarity protection	YES							
Over current/voltage protection	YES							
Anti-islanding protection	YES							
AC Short-circuit protection	YES							
Leakage current protecion	YES							
Grid monitoring	YES							
DC switch	YES							
Ingress protection	YES							
DC Surge protection	Type III							
AC Surge protection	Type III							
General								
Dimensions (W*H*D)	480*680*263.5mm / 18.9*26.8*10.4 in							
Weight	38kg / 83.8lbs			TBD				
Ingress protection rating	IP65							
Operating environment temperature range (°C)	-25~60							
Storage temperature range (°C)	-40~70							
Relative humidity	0~100%							
Display & Communication interface	Touch color screen, RS485/Wifi/CAN							
Warranty	5/10 years							
Cooling method	Natural cooling			Smart cooling				
Topology	Transformer-less							
Altitude	<4000m							
Noise emission (typical)	<50dB							
Standards & Certification								
EN62109-1/-2, CEI 2024								

Model	
Scalable Connection	2~8pcs series per stack, up to 20 stack parallel
Battery module nominal voltage	70.4V
Battery module nominal capacity	72Ah
Battery module nominal energy	5.069kWh
Protection	IP65
Battery module voltage range	61.6V~80.3V
Recommend charge/discharge current	36A, 0.5C per battery module
Max continuous charge/discharge current	50.4A, 0.7C per battery module
Max continuous charge/discharge power	3.548 kW per battery module
Max. series number per cluster	8 series
Cluster parallel	Up to 20 clusters, without extra unit needed
Charging/Discharging temperature	0 ~ +55 ℃, -20 ~ +55 ℃
Recommend storage temperature	-10 ~ +35 ℃ (Max. range -30 ~ +55 ℃)
Recommend storage humidity	10% ~ 90% RH
Warranty *	10 years, 6000 cycles
Certification	CE UN38.3; IEC62619
Remote Maintenance	Flexible remote upgrade, Original firmware backup to prevent upgrade failure

@25℃, 90% DOD. 0.5C testing condition

Battery Capacity	Voltage	Weight	Dimension
10kWh	140.8V	110kg / 242.5lbs	736*577*382mm / 29.0*22.7*15.0 in
15kWh	211.2V	155kg / 341.7lbs	736*735*382mm / 29.02*28.9*15.0 in
20kWh	281.6V	200kg / 440.9lbs	736*893*382mm / 29.0*35.2*15.0 in
25kWh	352V	245kg / 540.1lbs	736*1051*382mm / 29.0*41.4*15.0 in
30kWh	422.4V	290kg / 639.3lbs	736*1209*382mm / 29.0*47.6*15.0 in
35kWh	492.8V	335kg / 738.6lbs	736*1367*382mm /29.0*53.8*15.0 in
40kWh	563.2V	380kg / 837.8lbs	736*1525*382mm / 29.0*60.0*15.0 in